


TRIVISIO

Specification Sheet – Colibri Wireless



GENERAL DESCRIPTION

Colibri Wireless is the Inertial Measurement Unit (IMU). It carries 3 -axis state-of -art sensors to measure acceleration, angular rate and magnetic field. Built-in temperature sensor helps to eliminate temperature influences on other sensors.

Up to 10 Colibri-Wireless could be connected in the synchronous network to the single USB-dongle (receiver). Several networks may be synchronized via cable.

Sampling frequency is 100 Hz for every tracker.
Supplied API for Windows and Linux implements orientation tracker.



FEATURES

3-axis MEMS accelerometer
3-axis MEMS gyroscope
3-axis magneto-resistive sensor
Temperature sensor

2.4 GHz band operation
10 meters working distance
16 hours operation with built-in battery micro-USB charging
Up to 10 trackers synchronized in the wireless Network

USB-dongle (receiver), with USB interface (Virtual COM-port) and synchronization IN/OUT to join 2 or more Colibri networks

Sync output (for OEMs, e.g. to synchronize with a camera)

Software API is usable with Windows and Linux Colibri can output orientation data in quaternion form



SPECIFICATIONS

Accelerometer	Scale:	±6 g
	Resolution:	13-bit
Gyroscope	Scale:	±2000 °/s
	Resolution:	16-bit
Magnetic sensor	Scale:	±1.3 Ga
	Resolution:	12-bit
Temperature sensor	Accuracy:	±0.5 °C
Operation Temperature	0..+55 °C (self-powered) 0..+40 °C (charging)	
Working frequency	100 Hz	
Orientation accuracy	Pitch/roll: 0.5 °	
	Yaw:	2.0 °
Non-volatile memory for user data	1024 bytes	
Power consumption	3.7V Li-Pol battery 595mAh	
	40 mA	
Dimensions	56 x 42 x 17 mm	
Weight	41 grams	



Lux Prototyping S.A.R.L.
23, rue des Bateliers,
6713 Grevenmacher
Luxembourg

Tel: +352-26714533
Fax: +352-26714534
Email: info@trivisio.com
Web: www.trivisio.com