



LSC44-37 (Scout)

- Head Mounted Display -

1. Technical Characteristics

The Scout HMD is a specialized product designed for Virtual Reality applications. It is an opto-electronic device that projects an image or streams video through near-the-eye micro-displays.

The device is equipped with two micro light crystal displays (LCDs) attached to magnifying optical elements of high quality for each eye.

2. Technical Specifications

Micro Displays	2 x SVGA LCD 800 x 600 x 3 color
Display Color	24 bit
Frame Rate	60 fps
Contrast Ratio	130:1 (typical)
Overlap	100 %
Field of View	38° - 40° diagonal
Distortion	< 3%
Eye distance (IPD)	58 – 70 mm adjustable
Eye Relief	27 mm
Eye Motion Box	8 mm (h) x 6 mm (v)
Video Interface	DVI-D or HDMI
Audio	3.5 mm socket for headset
Cable Length (max)	15 ft (~ 4.57 m)
Power Consumption	2.5 W (5 V, 500 mA from USB port)
Operating Temperature	0° C to +60° C (operating temperature display)
Weight	210 g (without headband)
Dimensions (W/H/D)	150 mm x 53 mm x 52 mm

Subject to technical modifications

3. How to operate the Scout

- 1) Connect the DVI-D or HDMI (depends on ordered version) plug to the graphic-card output of your PC.
- 2) Connect the USB plug, which comes from the connection-dongle to the PC. This will power out the Scout.

To disconnect the Scout from your computer, perform the above steps in reverse order.



Lux Prototyping S.A.R.L.
23, rue des Bateliers,
6713 Grevenmacher
Luxembourg

Tel: +352-26714533
Fax: +352-26714534
Email: info@trivisio.com
Web: www.trivisio.com